

**DS-2CE56D0T-IT1E**  
**2 MP PoC Fixed Turret Camera**



- 2 MP PoC turret camera
- EXIR 2.0: advanced infrared technology with 20 m IR distance
- Water and dust resistant (IP67)
- Transmits both HD video and power over the same coaxial cable

## ▪ Specification

| Camera                    |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| Image Sensor              | 2.0 megapixel progressive scan CMOS                                       |
| Max. Resolution           | 1920 (H) × 1080 (V)                                                       |
| Min. Illumination         | 0.01 Lux@(F2.0, AGC ON), 0 Lux with IR                                    |
| Shutter Time              | PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s                      |
| Day & Night               | IR Cut Filter                                                             |
| Angle Adjustment          | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°                       |
| Signal System             | PAL/NTSC                                                                  |
| Lens                      |                                                                           |
| Lens Type                 | 2.8 mm, 3.6 mm and 6 mm fixed focal lens                                  |
| Focal Length & FOV        | 2.8 mm, horizontal FOV: 103.55°                                           |
|                           | 3.6 mm, horizontal FOV: 82.63°                                            |
|                           | 6 mm, horizontal FOV: 54.38°                                              |
| Lens Mount                | M12                                                                       |
| Illuminator               |                                                                           |
| Supplement Light Range    | Up to 30 m                                                                |
| Image                     |                                                                           |
| Image Settings            | Brightness,Sharpness,AGC                                                  |
| Frame Rate                | PAL: 1080P@25fps<br>NTSC: 1080P@30fps                                     |
| Day/Night Mode            | Auto/Color/BW (Black and White)                                           |
| Image Enhancement         | BLC,HLC,Global                                                            |
| Noise Reduction           | 2D DNR                                                                    |
| Supplement Detection(PIR) |                                                                           |
| PIR Range                 | Up to 20 m                                                                |
| Interface                 |                                                                           |
| Video Output              | 1 HD analog output                                                        |
| General                   |                                                                           |
| Power                     | 12 VDC ±30%/PoC.af, max. 4 W                                              |
| Material                  | Plastic                                                                   |
| Dimension                 | 110 mm × 93.2 mm (4.33" × 3.67")                                          |
| Weight                    | Approx. 350 g (0.77 lb.)                                                  |
| Operating Condition       | -40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing) |
| Communication             | HIKVISION-C                                                               |
| Language                  | English                                                                   |
| Approval                  |                                                                           |
| Protection                | IP67                                                                      |

## ▪ Available Model

DS-2CE56D0T-IT1E(2.8mm)

DS-2CE56D0T-IT1E(3.6mm)

DS-2CE56D0T-IT1E(6mm)

DS-2CE56D0T-IT1E(2.8mm)/SKD

DS-2CE56D0T-IT1E(3.6mm)/SKD

▪ **Accessory**

▪ **Optional**

| DS-1272ZJ-110-TRS<br>Wall Mount                                                     | DS-1275ZJ-SUS<br>Vertical Pole Mount                                               | DS-1276ZJ-SUS<br>Corner Mount                                                      | DS-1280ZJ-S<br>Junction Box                                                           | DS-1281ZJ-S<br>Inclined Ceiling<br>Mount                                             |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |  |  |  |
| DS-1280ZJ-TR13                                                                      |                                                                                    |                                                                                    |                                                                                       |                                                                                      |
|  |                                                                                    |                                                                                    |                                                                                       |                                                                                      |



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq