# SMB Solution for Offices

Grow your business with one-stop SMB solutions

## Core **Benefits**

### For installers

- One-stop procurement and management
- Less maintenance cost with remote troubleshooting

### For end-users

- One software for all devices
- Less costs with no need for servers / VPN
- Digital management for employees & visitors
- Robust protection against theft

## How Our **Solution Works**

### Control Room



**AcuSeek NVR**



**Management software**

- Unified management of diverse systems
- Easy management on portal / app
- Temporary pass for visitor access
- Search with text or voice



### Working Area



**Video security**



**Alarm**



**Access Point**

- Instant intrusion alerts, smart and rapid incident search
- Fast Wi-Fi connection for working

### Meeting Room



**Interactive flat panel**

- Paperless discussion and meeting

### Perimeter Area



**Video security**

- Intrusion alerts with audio-visual alarm

### Lobby



**Speed gate**



**Access terminal**

- Touch-free employee access
- Digital management of attendance, leave & business trip

### Entrance



**ANPR camera**



**Barrier gate**



**Radar**

- Non-stop vehicle pass
- Easy deployment & precise recognition

# Product **Showcase**

## Cloud-based Software

### Hik-Partner Pro
For installers

- Remote health monitoring and troubleshooting on portal / app

### Hik-Connect
For end-users

- Remote monitoring and management on portal / app
- Free access* (channels, doors, ANPRs, panels) to cover most SMB scenes

**Quantity varies by region. Contact local provider for details.*

Scan to download

## Video Security

### Analog solution



#### Turbo HD Camera
DS-2CE78D0T-L(X)TS

- 2 MP
- Two-way audio
- Smart Hybrid Light
- 20 m white light and 25 m IR



#### Turbo HD Camera with ColorVu
DS-2CE72DF3T-LXTS

- 2 MP
- Two-way audio
- Smart Hybrid Light
- IR / white light up to 40 m
- WDR ≥ 120 dB
- IP67



#### PowerX DVR
iDS-7208HQHI-M1/XT

- 8-ch Motion Detection 2.0
- 4-ch perimeter protection
- 8-ch AcuSearch
- All channels two-way audio

### IP solution



#### Network Camera with ColorVu
DS-2CD1147G3H-LIUF

- HikAI-ISP, 4 MP
- ColorVu 3.0, Motion Detection 3.0, Smart Hybrid Light
- 0.0001 lux @ F1.0
- IR/white light up to 30 m
- IP67, IK08



#### Network Camera with ColorVu
DS-2CD2T47G3-LIS2UY/SL

- 4 MP
- ColorVu 3.0, AcuSense 3.0, Smart Hybrid Light
- Two-way audio, built-in dual-microphone
- Strobe light and audio alarm
- IR / white light up to 60 m
- IP67, NEMA 4X anti-corrosion



#### AcuSeek NVR
DS-7616NXI-K1/VPro

- 16-ch IP video input; /P: PoE
- Up to 24 × 1080p decoding capability
- Full Channel AcuSeek for IPC with ColorVu 3.0 /AcuSense

## Access Control



#### MinMoe Face Recognition Terminal
DS-K1T342 Series

- 4.3-inch touch screen
- Max. 1500 faces
- Face recognition < 0.2 s / user
- IP65, PoE, video intercom



#### MinMoe Face Recognition Terminal
DS-K1T344 Series

- 4.5-inch touch screen
- Max. 3,000 faces
- Face recognition < 0.2 s / user
- IP65, PoE, video intercom



#### Speed Gate
DS-K3B211LX series

- 4 pairs of infrared sensors
- Lane width: 550 mm to 900 mm
- MCBF > 3 millions times



#### Barrier Gate
DS-TMG32 series

- Max. rising speed 3 m @ 3 s, DC brushless motor
- MCBF: 2.5 million times
- App-based configuration via Bluetooth



#### ANPR Camera
DS-TCG406 Series

- 2688 × 1520 resolution
- 4 built-in LEDs (integrated white light and IR)
- LPR accuracy > 98%
- IP67, IK10



#### Anti-fall Radar
DS-TMG035 Series

- Response time 50 ms
- Detection area 0-2 m
- IP67

## Alarm



#### AX PRO Kit
DS-PWA64-Kit-WE/WB

- Includes 1 panel, 1 keyfob, 1 PIR detector, and 1 magnetic contact
- Up to 64 wireless zones/outputs (including 48 PIRCAMs)
- LAN, Wi-Fi, GPRS (Single SIM Card)



#### Wireless Smoke Detector
DS-PD451SMK-WE/WB

- Smoke & Heat
- Detection range: 30-80 m², 4-12 m
- Buzzer ≥ 85 dB @ 3 m
- Up to 1,000 m transmission range
- Up to 5 years battery life

## Networking and Display



#### Ceiling Access Point
DS-3WAP6230-EI

- Wi-Fi 6 dual band 3000 Mbps
- 2 x Gigabit ports with 1 PoE input
- Users (Max. / Recommend): 256 / 110



#### PoE Gateway Router
DS-3WG1510P-EI

- 8 Gigabit PoE ports, 2 Gigabit WAN ports
- Max. 1000 Mbps throughput
- Users: 100
- PoE power budget 60 W



#### Smart Managed Switch
DS-3E1528P-EI

- 24 x Gigabit PoE RJ45 ports, 2 × Gigabit RJ45 ports, 2 x Gigabit fiber optical ports
- Total PoE power budget 370 W



#### Interactive Flat Panel
DS-D5C75RB/B2L

- 4K display
- 75-inch touch screen
- Dual systems of Android and Windows



#### Monitor
DS-D5022F2

- 1080p
- 21.5"
- HDMI, VGA, Audio out