SMB Solution for Villas

Grow your business with one-stop SMB solutions

Core **Benefits**

For installers

- One-stop procurement and management
- Less maintenance cost with remote troubleshooting
- Easy Installation

For end-users

- One software for all devices
- Less costs with no need for servers / VPN
- Vehicle gate automatic unlocking
- High-level protection to deter theft

How Our **Solution Works**

Indoor Area


Video security


Intercom


Alarm system


Mesh Wi-Fi System

- Theft prevention via video security & alarm detection
- Video intercom to unlock doors for visitors
- Fire detection and alarm for family safety
- High-speed Wi-Fi for the whole home stable connection

Remote Control


Management software

- Unified management of diverse systems
- Live view check, doors unlocking, intercom via mobile app



Perimeter Area


Video security
(AOV SolarVu Cameras)

- 24/7 Continuous recording, always-on video
- Accurate intrusion alerts with strobe light and audio alarm and two-way audio
- Easy installation with no wiring required

Yard


Video security
(EasyLink Wi-Fi Kit)

- Robust protection of properties and assets
- Easy installation with no network cable required

Entrance


Video Intercom


Gate Opener

- Remote opening and automatic access for family members, visitors, and vehicles
- Video intercom linked gate opening

Product **Showcase**

Cloud-based Software

Hik-Partner Pro
For installers

- Remote health monitoring and troubleshooting on portal / app

Hik-Connect (Personal Mode)
For end-users

- Remote monitoring and management on app

Scan to download

Video Security

Wireless Solution



AOV Solar Camera
DS-2CFS04/4G

- 4 MP, 1/3" CMOS
- 0.005 lux @ F1.6
- IR / white light up to 30 m
- Motion Detection 2.0
- Two-way audio
- IP66



AOV Solar Camera
DS-2CFSP4/4G

- Dual 4 MP, 0.005 lux@F1.6
- Panoramic view + detailed view
- Smart Hybrid Light: IR / white light up to 30 m
- Motion Detection 2.0
- Strobe light and audio alarm
- Two-way audio
- IP66



2 MP Wi-Fi Bullet Camera
3 MP Wi-Fi PT Turret Camera
4-ch NVS

EasyLink Wi-Fi NVS Kit
NKS4223WBTH

- Smart Hybrid Light
- Two-way audio
- Smart tracking (PT Camera)
- One-tap privacy mode (PT Camera)
- 2 Micro SD card slots, up to 512GB each
- 4-ch IP video input

Wired Solution



Network Camera with ColorVu
DS-2CD1047G3-LIU(F)(/SL)(/SRB)

- Strobe light & audio alarm, two-way audio, Smart Hybrid Light
- HikAI-ISP, 4 MP
- 0.0005 lux @ F1.0
- IR / white light up to 30 m
- IP67



Network Camera with ColorVu
DS-2CD1147G3-LIUF

- HikAI-ISP, 4 MP
- ColorVu 3.0, Motion Detection 3.0, Smart Hybrid Light
- 0.0005 lux @ F1.0
- IR / white light up to 30 m
- IP67, IK08



NVR with AcuSense
DS-7608NXI-K1(/8P)(E)

- 8-ch IP video input; /P: PoE
- Up to 10 × 4 MP / 20 × 1080p decoding capability
- 8-ch AcuSearch
  2-ch perimeter protection

Video Intercom and Gate Opener



Hybrid HD Intercom Kit
DS-KIS313 Series

- Includes 1 indoor station, and 1 outdoor station
- App control
- Hybrid connection, plug & play



IP Video Intercom Kit
DS-KIS613-S

- 1 indoor station: 7" touch screen
- 1 door station: 4 MP, 150° FOV
- App control
- IP connection



Sliding Gate Opener
DS-K3GL606 Series

- Gate mass ≤ 600 kg
- Support Wi-Fi and LAN
- Open gate via keyfob, app, intercom, etc.

Alarm



AX PRO Kit
DS-PWA64-Kit-WE/WB

- Includes 1 panel, 1 keyfob, 1 PIR detector, and 1 magnetic contact
- Up to 64 wireless zones / outputs (including 48 PIRCAMs)
- LAN, Wi-Fi, GPRS (Single SIM card)



Wireless PIRCAM Detector
DS-PDPC12P-EG2-WE(B)/WB(B)

- Detection range: 12 m / 85.9°
- Up to 20 pictures for verification
- 800 m transmission distance
- Up to 5 years battery life



Wireless Smoke Detector
DS-PD451SMK-WE/WB

- Smoke & Heat
- Detection range: 30-80 ㎡, 4-12 m
- Buzzer ≥ 85 dB @ 3 m
- Up to 1,000 m transmission range
- Up to 5 years battery life



Wireless Portable Emergency Button
DS-PDEBP1-EG2-WE(B)/WB(B)

- Fully remote configurable through app
- IP66 waterproof



Wireless PIR Glass Break Detector
DS-PDPG12P-EG2-WE/WB

- PIR detection range: 12 m / 85.9°
- Glass break detection range: 8 m / 120°
- Up to 30 kg pet immunity

Networking, Display and Accessory



Mesh Wi-Fi System
DS-3WRM12GC Series

- AC1200M dual-band, Wi-Fi 5
- One-tap mesh: auto-pair devices
- Seamless roaming
- Dual app management via Hik-Connect & Hik-Partner Pro



Smart Managed Switch
DS-3E1309P-EI (B)

- 10/100 M PoE port: 8
- Gigabit RJ45 port: 1
- Total PoE power budget 110 W



Online UPS
DS-UPS01K24-R/TS

- Capacity 1000 VA / 900 W, PF up to 0.9
- Easy management with local and remote monitoring
- Surge / short circuit / overcharge / over discharge protection and Emergency Power Off function (EPO)